ABR7S11

plug-in electromechanical relay - 5 mm - 24 V DC - 1 NO



Main

Advantys Telefast ABE7
Plug-in electromechanical relay
DC
Set of 4

Complementary

Width pitch dimension	0.20 in (5 mm)
Product Compatibility	ABE7R16T111 ABE7R16M111 ABE7P16M111 ABE7P16T111
[Uc] control circuit voltage	24 V
[Ith] conventional free air thermal current	6 A
Contacts type and composition	1 NO
Threshold tripping voltage	16.8 V 104 °F (40 °C)
Drop-out voltage	2 V 68 °F (20 °C)
Drop-out current	0.5 mA 68 °F (20 °C)
Maximum power dissipation per pole	0.17 W
Associated fuse rating	1 A, fast blow
Maximum switching voltage	250 V AC 50/60 Hz IEC 60947-5-1 30 V DC IEC 60947-5-1
Electrical durability	500000 Cycles 2000 mA 230 V AC-12 500000 Cycles 3000 mA 24 V DC-12 500000 Cycles 400 mA 230 V AC-15 500000 cycles 500 mA 24 V DC-13 10 ms
Minimum switching current	100 mA >= 5 V
Operating rate in Hz	20 Hz no load 0.1 Hz at le
Mechanical durability	20000000 cycles
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-1
Net Weight	0.01 lb(US) (0.005 kg)

Environment

Max immunity to microbreaks	1 ms
Dielectric strength	4000 V IEC 60947-1

Ordering and shipping details

000	
CP2	
3389110251470	
1	
0.25 oz (7 g)	
_	3389110251470 1

Returnability	No
Country of origin	LV
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	0.31 in (0.8 cm)
Package 1 width	0.94 in (2.4 cm)
Package 1 Length	5.91 in (15 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Weight	1.02 oz (29 g)
Package 2 Height	0.31 in (0.8 cm)
Package 2 width	0.94 in (2.4 cm)
Package 2 Length	5.91 in (15 cm)
Unit Type of Package 3	S01
Number of Units in Package 3	200
Package 3 Weight	3.64 lb(US) (1.652 kg)
Package 3 Height	5.91 in (15 cm)
Package 3 width	5.91 in (15 cm)
Package 3 Length	15.75 in (40 cm)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and
	lead compounds, which is known to the State of California to cause cancer
	and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	
LO RONS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes
Contractual warranty	

Warranty	18 months