Product Specifications



Electrical Specifications	Optifuse P/N	Current Rating	
600VAC – 1A - 30A			
600VDC – 1A - 30A	FPK-1A	1A	
	FPK-1.25A	1.25A	
Standards	FPK-1.5A	1.5A	
	FPK-1.6A	1.6A	
1A-30A - UL Listed to Standard 248-14. File E197390 1A-30A - CSA Certified Standard C22.2 No. 248.14. File E197390	FPK-2A	2A	
1A-30A - C3A Certifieu Staliuaru C22.2 No. 246.14. File L197.390	FPK-2.5A	2.5A	
Supplementary Protection Only – Not rated for branch circuit protection	FPK-3A	3A	
	FPK-3.15A	3.15A	
Interventing Dating	FPK-3.5A	3.5A	
Interrupting Rating	FPK-4A	4A 5A 6A	
100,000 amperes at 600V AC(1A-30A) 10,000 amperes at 600V DC(1A-30A)	FPK-5A		
	FPK-6A		
	FPK-6.3A	6.3A	
	FPK-7A	7A	
Mechanical Dimensions: Inches [mm]	FPK-8A	8A	
	FPK-9A	9A	
	FPK-10A	10A	
Ø0.40±0.004	FPK-12A	12A	
[10.3±0.1]	FPK-15A	15A	
	FPK-16A	16A	
	FPK-20A	20A	
	FPK-25A	25A	
	FPK-30A	30A	
1.50±0.02[38.0±0.6]			

Time vs. Percent of Rated Current



Part Numbers Information

Class M Midget Fuse - Fast Acting 13/32" x 1 1/2"		FPK				
Rev	Rev Date of issue Revision Notes			Designed Approved		
А	01-02-2022	Initial Drawing		RC	OF	