

# ON Semiconductor

## Is Now

# onsemi™

To learn more about onsemi™, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)

---

**onsemi** and **onsemi** and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi** product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner. Other names and brands may be claimed as the property of others.

# BF256A

BF256A is a Preferred Device

## JFET - General Purpose

### N-Channel

N-Channel Junction Field Effect Transistor designed for VHF and UHF applications.

- Low Cost TO-92 Type Package
- Forward Transfer Admittance,  $Y_{fs} = 4.5$  mmhos (Min)
- Transfer Capacitance –  $C_{RSS} = 0.7$  (Typ)
- Power Gain at  $f = 800$  MHz, Typ. = 11 dB

#### MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	30	Vdc
Drain-Gate Voltage	$V_{DG}$	30	Vdc
Gate-Source Voltage	$V_{GS}$	30	Vdc
Forward Gate Current	$I_{G(f)}$	10	mAdc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	360 2.88	mW mW/ $^\circ\text{C}$
Operating and Storage Channel Temperature Range	$T_{channel}$ , $T_{stg}$	-65 to +150	$^\circ\text{C}$






Figure 1. Power Derating Curve




ON Semiconductor™

<http://onsemi.com>



TO-92  
CASE 29  
STYLE 5

#### MARKING DIAGRAMS



Y = Year  
WW = Work Week

#### ORDERING INFORMATION

Device	Package	Shipping
BF256A	TO-92	5000 Units/Box

Preferred devices are recommended choices for future use and best overall value.

# BF256A

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

### OFF CHARACTERISTICS

Gate-Source Breakdown Voltage	(-I <sub>G</sub> = -1.0 μAdc, V <sub>DS</sub> = 0)	-V <sub>(BR)GSS</sub>	30	-	-	Vdc
Gate-Source Voltage	(V <sub>DS</sub> = 15 Vdc, I <sub>D</sub> = 200 μA)	-V <sub>GS</sub>	0.5	-	7.5	Vdc
Gate Reverse Current	(-V <sub>GS</sub> = 20 Vdc, V <sub>DS</sub> = 0)	-I <sub>GSS</sub>	-	-	5.0	nAdc


### ON CHARACTERISTICS

Zero-Gate-Voltage Drain Current (Note 1.)	(V <sub>DS</sub> = 15 Vdc, V <sub>GS</sub> = 0)	I <sub>DSS</sub>	3.0	-	7.0	mAdc
---	---	------------------	-----	---	-----	------


### SMALL-SIGNAL CHARACTERISTICS

Forward Transfer Admittance	(V <sub>DS</sub> = 15 Vdc, V <sub>GS</sub> = 0, f = 1 kHz)	Y <sub>fs</sub>	4.5	5.0	-	mmhos
Reverse Transfer Capacitance	(V <sub>DS</sub> = 20 Vdc, -V <sub>GS</sub> = 1 Vdc, f = 1 MHz)	C <sub>rSS</sub>	-	0.7	-	pF
Output Capacitance	(V <sub>DS</sub> = 20 Vdc, V <sub>GS</sub> = 0, f = 1 MHz)	C <sub>oss</sub>	-	1.0	-	pF
Cut-Off Frequency (Note 2.)	(V <sub>DS</sub> = 15 Vdc, V <sub>GS</sub> = 0)	f <sub>gfs</sub>	-	1000	-	MHz

1. Pulse Test: Pulse Width = 300 μs, Duty Cycle = 2.0%.
2. The frequency at which g<sub>fs</sub> is 0.7 of its value at 1 KHz.



**Figure 2. Correlation Between  
-V<sub>GS(off)</sub> and I<sub>DSS</sub>**



**Figure 3. Drain Current versus  
Drain-to-Source Voltage**




Figure 4. Input Admittance versus Frequency




Figure 5. Forward Transfer Admittance versus Frequency




Figure 6. Reverse Transfer Admittance versus Frequency




Figure 7. Output Admittance versus Frequency




Figure 8. Input Capacitance versus Gate-Source Voltage





Figure 9. Reverse Transfer Capacitance versus Gate-Source Voltage

# BF256A

## PACKAGE DIMENSIONS

### TO-92 (TO-226) CASE 29-11 ISSUE AL



#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---

**ON Semiconductor** and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

#### PUBLICATION ORDERING INFORMATION

##### Literature Fulfillment:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: ONlit@hibbertco.com

**N. American Technical Support:** 800-282-9855 Toll Free USA/Canada

**JAPAN:** ON Semiconductor, Japan Customer Focus Center  
4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031  
Phone: 81-3-5740-2700  
Email: r14525@onsemi.com

**ON Semiconductor Website:** <http://onsemi.com>

For additional information, please contact your local Sales Representative.