Contact IDT | Investors | Press

About IDT

Products

Applications

Support

mylDT

Calculators | Cross Reference | Green Initiative | Military | Parametric Search | Search by Part Number, Keyword, Document, Green/Pb-Free, Package

Home > Products > > 960010 > 960010AFLF

960010AFLF

Category:

Generic Part: 960010

Market Group: PC CLOCK

Description: PC SPECIAL PURPOSE

Features:

• CPU, ASIC, and PCI can run at 2.5V or 3.3V selectable.

• 1-CPU (2.5V/3.3V) (66.66MHz to 100.00MHz)

• 2-PCI (2.5V/3.3V) (33.33MHz)

• 2-ASIC (2.5V/3.3V) (66.66MHz to 100.00MHz)

• 1-ASIC (2.5V/3.3V) (33.33MHz to 100.00MHz)

• 1-12MHz (3.3V)

You may also like...



Parameters

| Speed | NA |
|-------------------------|--------|
| Temperature | С |
| Voltage | 3.3 V |
| Status | Active |
| Sample | Yes |
| Minimum Order Quantity | 141 |
| Factory Order Increment | 47 |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

| Туре | Title | Size | Revision Date |
|------|------------------------|-------|---------------|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007 |

Package

| · · | |
|----------------------------------|--------------------------|
| Package | SSOP 28 (PYG28) |
| Description | SSOP 5.3 MM |
| Status | Active |
| Class | PLASTIC |
| Category | Green |
| Pb (Lead) Free | Yes |
| Mark | F |
| Package Type | SSOP |
| Lead Count | 28 |
| Length | 10.2 mm |
| Width | 5.3 mm |
| Thickness | 1.73 mm |
| Pitch | 0.65 mm |
| Tube / Tray | TUBE |
| Quantity per Tube/Tray | 47 |
| Quantity per Reel | 1000 |
| Moisture Sensitivity Level (MSL) | 1 |
| Moisture Exposure Floor Life | Unlimited@<30C/85% RH |
| Peak Reflow Temperature | 260°C |
| Rebake Conditions | NA |
| Related Package Documents | view documents |