



NOTES:

1. TO BE USED WITH 11W07-W11 OR 12W07-W11 JACKS.
2. HANDLE MATERIAL: PLASTIC
3. HANDLE COLOR: BLACK
4. IP RATING: IP66
5. RECOMMENDED WORKING TEMPERATURE: -20TO 50 °C.
6. THE PLUG MUST BE TIGHTEN ALL THE WAY INTO THE HANDLE.
7. RoHS COMPLIANT.

PART NUMBER	CABLE OD MIN.	CABLE OD MAX.
250S15	0.140"	0.170"
250S18	0.170"	0.200"
250S22	0.200"	0.230"
250S25	0.230"	0.260"
250S28	0.260"	0.290"

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE *	WIDTH *	MULT *	LBS/M *	TEMPER *
					FINISH *			MATERIAL *	
					SPEC No. *			SPEC No. *	
					FIRST USED ON *		SCALE 1:1		
0A	PRELIMINARY	2/17/20	NS	SRC	DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft®</b>
REV	ECO NUMBER	DATE	BY	APVD	02/17/20	NS	NS	SRC	
REVISIONS					DO NOT SCALE DRAWING				
					NAME			PART No.	
					SEALED 1/4" PLUG			250S15-S28	
								REV 0A	