



Delta 6A

GSM/GPRS, 3G & ISM Hinged Antenna SMA Male

Key Features

- Quad band GSM GPRS frequency
- 6.78 dBi peak gain
- ISM: 868 and 915MHz
- 3G: 2100MHz



General Description

The Delta6A multi-band whip antenna has excellent performance in the quad band GSM 800/900/1800/1900 frequencies.

Terminated with an SMA Male or SMA-RP (reverse polarity) Male connector. The knuckle joint allows for antenna position adjustment through a 0, 45 & 90 degree angles and then swivels to allow vertical positioning.

Common IoT applications include: car park / utilities metering, wireless key entry, security systems, remote monitoring and many other IoT applications.

Additional Considerations

- Fits to most popular GSM / GPRS and 3G terminal equipment
- Adjustable mount allows positioning for best signal
- Does not rely on mounting on metallic surface
- Meets all EU compliance criteria for electronic goods





Delta 6A


GSM/GPRS, 3G & ISM Hinged Antenna SMA Male

Electrical Specifications

Operating temperature range:	-20 - +65 °C
Impedance:	50 Ohm
Operating Frequencies:	850, 900, 1800, 1900MHz (Quad Band GSM/GPRS) 2100MHz (3G / UMTS) 868MHz, 915MHz (ISM)
Polarization:	Vertical
VSWR:	880MHz - 2.93dB 960MHz - 1.77dB 1710MHz - 2.72 dB 1990MHz - 1.72dB

Mechanical Specifications

Dimensions:	L196 x 13mm Ø
Connector:	SMA
Cable:	RG316 (Internal)
Mounting Method:	Direct connect



Return Loss






Delta 6A

GSM/GPRS, 3G & ISM Hinged Antenna SMA Male

VSWR



Ordering Details

Part number	Description
DELTA6A/X/SMAM/S/S/11	GSM/GPRS, 3G & ISM Hinged Antenna SMA Male

Registered in England No. 08405712
VAT Registration No. GB163 04 0349

Siretta Ltd
Basingstoke Road
Spencers Wood
Reading
Berkshire RG7 1PW

sales +44(0)118 976 9014
fax +44(0)118 976 9020
email sales@siretta.com
web www.siretta.com

Rev 1.8