# XCKJ1305955

Limit switch, XC Standard, XCKJ, steel roller plunger reinforced, 600 V AC, 10 A



#### Main

Range of Product	Telemecanique Limit switches XC Standard	
Series name	Standard format	
Product or Component Type	Limit switch	
Device short name	XCKJ	
Material	Metal	
Body Material	Zamak	
Head material	Zamak	
Fixing Mode	By the body	
Contact operation	Snap action	

#### Complementary

Complementary	
Contacts insulation form	Zb
Number of steps	1
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	300 VUL 508 500 V 3)IEC 60947-1 300 VCSA C22.2 No 14
Maximum resistance across terminals	25 MOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13, inductive, 120 V, 4 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13, inductive, 24 V, 10 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13, inductive, 48 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	1.69 in (43 mm)
Height	3.31 in (84 mm)
Depth	1.42 in (36 mm)
Net Weight	1.00 lb(US) (0.455 kg)
Terminals description ISO n°1	(11-12)NC (13-14)NO

#### Environment

Shock resistance	50 gn 11 ms IEC 60068-2-27	
Vibration resistance	25 gn 10500 Hz)IEC 60068-2-6	
IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK07 EN 50102	
Overvoltage category	Class I IEC 61140 Class I NF C 20-030	
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Protective treatment	TH	

Product Certifications	CCC UL CSA	
Standards	UL 508 IEC 60947-5-1	
	EN 60947-5-1	
	EN 60204-1	
	CENELEC EN 50041	
	IEC 60204-1	
	CSA C22.2 No 14	

## Ordering and shipping details

Category	22411-LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	Т
GTIN	3606485369648
Nbr. of units in pkg.	1
Package weight(Lbs)	16.58 oz (470.0 g)
Returnability	No

## Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.42 in (3.6 cm)	
Package 1 width	1.65 in (4.2 cm)	
Package 1 Length	4.49 in (11.4 cm)	

### Offer Sustainability

onor odolamability		
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Not applicable, out of EU RoHS legal scope	
Environmental Disclosure	Product Environmental Profile	