


Specification

Part Number: TM141037

Description: Omni-Directional Electret Condenser Microphone

(Size: 6.0mm x 3.6mm)

RoHS Compliant



Revision	Date	Comments
A	June 21, 2017	Initial Release


1. ELECTRICAL SPECIFICATIONS

Standard Conditions		Basic Test Conditions	
Temperature	5 to 35°C	Temperature	20 ± 2°C
Humidity	45 to 85%	Humidity	63 to 67%
Air Pressure	86 to 106kPa	Air Pressure	86 to 106kPa

Parameter	SPEC	Unit
Directional Characteristic	Omnii-Directional	dB
Sensitivity	-38±3	dB
Impedance	2.2(Max)	kΩ
S/N Ratio (A weighted network)	60(Min)	dB
Maximum Input Sound Pressure Level	120	dB
Standard Operating Voltage	2.0	Vdc
Operating Voltage Range	1.0~10	Vdc
Decrease Voltage Characteristics(Vs=2.0 to 1.5V dc)	-3(Max)	dB
Current Consumption	500(Max)	μA
Standard Test Circuit	See Fig. 1	—
Frequency Response Characteristic	See Fig. 2	—
Memo	Standard test condition	RL=2.2kΩ, Vs=2.0V dc (@f=1kHz, Pin=1Pa, 0dB=1V/pa, L=50cm)


2. STANDARD TEST CIRCUIT

Fig.1



**3. TYPICAL FREQUENCY RESPONSE
IN ANECHOIC CHAMBER**

Fig.2



4. RELIABILITY

Item		Test conditions	Evaluation standard
1	Hi-Temp.Test	The microphone unit must be subjected to +80°C for 100 hours and exposed to room temperature for 3 hours.	After any of the tests, the sensitivity of the microphone unit shall not change more than ±3dB from initial value and shall keep its initial operation and appearance.
2	Low-Temp.Test	The microphone unit must be subjected to -40°C for 100 hours and exposed to room temperature for 3 hours.	
3	Humidity &Heat Test	The microphone unit must be subjected to +50°C, 90% RH-for 200 hours and exposed to room temp for 3 hours.	
4	Thermal Shock Test	The microphone unit must be subjected to following condition [+80°C 0.5H → room temp 1H→ -40°C 0.5H →room temp 1H]at 10cycle.	
5	Vibration Test	The microphone unit must be subjected to a procedure that it is vibrating for two hours from each of the three directions(x y z) with a frequency of 10-55Hz and a 1.52mm-high amplitude.	
6	Drop Test	The microphone unit must be subjected to a procedure that it is dropped on a slippery marble floor for 5 times from a 1.0-meter-height without package.	
7	Storage Temperature	-35°C~+70°C R.H .less than 90%	
8	Operating Temperature	-35°C~+70°C R.H. less than 90%	
9	ESD Protection	The test microphone must be discharged between each ESD exposure without ground(contact:±6KV,air:±8KV)	

NOTES:

All the soldering procedures upon microphones must be completed in a heat sink device. The temperature of the soldering iron must be limited to 340°C±20°C and the soldering time should not exceed 3 seconds.

Operators, the soldering fixture and the soldering iron must be statically grounded under each soldering process.