



		REVISIONS			
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1		FIRST RELEASED	APR-10-2020	BLINK	TOMMY









NOTES: (UNLESS OTHERWISE SPECIFIED)

1. MATERIAL:

SHELL: THERMOPLASTIC, UL94 V-0.

2. SPECIFICATIONS:

2.1, OPERATING TEMPERATURE: -40~125°C.

2.2, MATING CYCLES DURABILITY: 100 CYCLES MIN (MATING WITH PL000727).

2.3, RoHS COMPLIANT.

3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

QUANTITY PART NUMBER			DESCRIPTION				ITE			
MATERIALS LIST										
UNLESS OTHERWISE SPECIFIED  1) All dimensions are in metric(mm).		SIGNATURES DA		DATE	Amphenol					
Tolerances are as     PL DEC +0.30 I	as follows: Fractions ±1/64 Angles ±1°  = X	DRAWN:	BLINK	APR-10-2020						
2 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08		CHECKED:	ORION	APR-13-2020	Sine Systems - www.amphenol-sine.cor					
3) Note reference =		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036					
MATERIAL SPECIFICATI		APPROVAL:	TOMMY	APR-15-2020		Oiiiii				
PROCESS SPECIFICATIONS:  NEXT ASSY:		CUSTOMER:			4MM, FEMALE PLUG HOUSING FOR USE WITH PL000729, PRM SERIES™					
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL								
					B	TYPE	DWG NO: PL0007	28	A 1	
				SCALE: N	ONE		SHEET 1	of <b>1</b>		