## **SIEMENS**

Data sheet 3SB2455-2A



Lampholder, Wedge base W2 x 4.6 d, with soldering pins for soldering pin connection

product brand name	SIRIUS
product designation	Lampholder
product type designation	3SB2
Contact block/ lampholder	
socket design	W2 x 4.6d
number of lampholders	1
General technical data	
product function positive opening	No
product component	
• light source	No
suitability for integration	front element
type of voltage	
<ul> <li>of the operating voltage</li> </ul>	AC/DC
protection class IP	
• of the enclosure	IP40
of the terminal	IP00
vibration resistance according to IEC 60068-2-6	20 200 Hz: 5g
reference code according to IEC 81346-2	P
Substance Prohibitance (Date)	07/01/2006
operating voltage	
• at AC	
— at 50 Hz rated value	5 60 V
<ul><li>— at 60 Hz rated value</li></ul>	5 60 V
<ul> <li>at DC rated value</li> </ul>	5 60 V
Auxiliary circuit	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0
operational current at AC-12	
<ul><li>at 24 V rated value</li></ul>	10 A
<ul> <li>at 60 V rated value</li> </ul>	10 A
<ul> <li>at 110 V rated value</li> </ul>	10 A
at 230 V rated value	10 A
operational current at AC-15	
• at 24 V rated value	4 A
• at 110 V rated value	4 A
at 230 V rated value	4 A
operational current at DC-12	
• at 24 V rated value	6 A

<ul> <li>at 60 V rated value</li> </ul>	5 A	
<ul> <li>at 110 V rated value</li> </ul>	2.5 A	
at 230 V rated value	1 A	
operational current at DC-13		
at 24 V rated value	3 A	
<ul><li>at 60 V rated value</li></ul>	1.2 A	
<ul> <li>at 110 V rated value</li> </ul>	0.7 A	
• at 230 V rated value	0.3 A	
Connections/ Terminals		
type of electrical connection	solder pin connectors	
Ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	-25 +60 °C	
<ul> <li>during storage</li> </ul>	-40 +80 °C	
Installation/ mounting/ dimensions		
fastening method	clip-on	
height	19 mm	
width	18 mm	
depth	29 mm	
Certificates/ approvals		
General Product Approval		Declaration of Conformity













other

Confirmation

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2455-2A

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2455-2A

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB2455-2A

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SB2455-2A&lang=en

last modified: 1/6/2021 🖸