

ANT4000 WIRELESS / WIFI ANTENNA





Technical

Туре	Co-linear Dipole Array
Frequency Range	2300 - 2500 MHz
Impedance	50 Ω Nominal
Gain	6 dBi (+/- 0.5 dBi)
Max Power	20 Watts (CW) at 50°C
Ingress Protection	IP67
Polarization	Linear Vertical
VSWR	1.5:1 max
Connector	N type female
Operating Temp	-40°C to +85°C



DIMENSIONS

All dimensions are in millimeters.

Length: 325mm Weight: 350g Mounting Mast: Between 35-54mm diameter A wide range of wireless and other antennae are available from Sensata, including ATEX rated antennae for hazardous areas.

The ANT4000 is typically used when an outdoor antenna with a reasonable gain and good omni-directional properties is required.

The antenna is protected to IP67 and comes with a pole or wall-mounting bracket.

It has a normal 50 ohm impedance and a VSWR rating of <2.0.

For a full listing of devices available or technical assistance in choosing a suitable antenna please contact Sensata.

Features

- 6dBi 2.4GHz outdoor antenna
- High gain small size, IP67
- N-Type female connector
- 20W maximum power
- For higher gain call Sensata



Part Number: ANT4000 Impedance: 50 ohm Gain: 6dBi

Made in the UK

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS, OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, OUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

CONTACT US

EUROPE +44 (0)1202 897969 c3w_sales@sensata.com Cynergy3 Components Ltd. 7 Cobham Road, Ferndown Industrial Estate, Wimborne, Dorset, BH21 7PE, United Kingdom

USA +1 310 561 8092 / +1 866 258 5057 c3w_sales@sensata.com