



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE56028 TRIAC, 40 Amp

Description:

The NTE56028 is a 40 Amp TRIAC is a TO220 type package designed primarily for full-wave AC control applications such as lighting systems, heater controls, motor controls, and power supplies.

Features:

- Blocking Voltage of 800V
- All Diffused and Glass-Passivated Junctions for Parameter Uniformity and Stability
- Gate Triggering Guaranteed in Four Modes

Absolute Maximum Ratings:

| | |
|--|-------------------------------------|
| Peak Repetitive Off-State Voltage, V_{DRM} ($T_J = -40^\circ$ to $+125^\circ\text{C}$, 1/2 Sine Wave 50 to 60Hz, Gate Open, Note 1) | 800V |
| On-State RMS Current ($T_C = +75^\circ\text{C}$, Full Cycle Sine Wave 50 to 60Hz, Note 2), $I_T(\text{RMS})$ | 40A |
| Peak Non-Repetitive Surge Current ($T_J = +125^\circ\text{C}$, One Full Cycle, 60Hz), I_{TSM} | 350A |
| Circuit Fusing ($t = 8.3\text{ms}$), I^2t | 500A ² s |
| Peak Gate Current ($t \leq 2\mu\text{s}$), I_{GM} | $\pm 2\text{A}$ |
| Peak Gate Voltage ($t \leq 2\mu\text{s}$), V_{GM} | $\pm 10\text{V}$ |
| Peak Gate Power ($t \leq 2\mu\text{s}$), P_{GM} | 20W |
| Average Gate Power ($T_C = +75^\circ\text{C}$, $t \leq 8.3\text{ms}$), $P_{G(AV)}$ | 0.5W |
| Operating Junction Temperature Range, T_J | -40° to $+125^\circ\text{C}$ |
| Storage Temperature Range, T_{stg} | -40° to $+150^\circ\text{C}$ |
| Thermal Resistance, Junction-to-Case, R_{thJC} | 1°C/W |
| Thermal Resistance, Junction-to-Ambient, R_{thJA} | 60°C/W |
| Mounting Torque | 8in. lb. |

Note 1. Ratings apply for open gate conditions. Devices shall not be tested with a constant current source for blocking voltage such that the voltage applied exceeds the rated blocking voltage.

Note 2. This device is rated for use in applications subject to high surge conditions. Care must be taken to insure proper heat sinking when the device is to be used at high sustained currents.

Electrical Characteristics: ($T_C = +25^\circ\text{C}$ and either polarity of MT_1 to MT_2 voltage unless otherwise specified)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|--|------------|--|-------------------|------|------|------------------------|
| Peak Forward Blocking Current | I_{DRM} | $V_{DRM} = 800\text{V}, T_J = +25^\circ\text{C}$ | - | - | 10 | μA |
| | | $V_{DRM} = 800\text{V}, T_J = +125^\circ\text{C}$ | - | - | 2 | mA |
| Peak Reverse Blocking Current | I_{RRM} | $V_{RRM} = 800\text{V}, T_J = +25^\circ\text{C}$ | - | - | 10 | μA |
| | | $V_{RRM} = 800\text{V}, T_J = +125^\circ\text{C}$ | - | - | 2 | mA |
| Peak On-State Voltage | V_{TM} | $I_{TM} = 56\text{A}$ (Peak), Note 3 | - | 1.40 | 1.85 | V |
| Gate Trigger Current (Continuous DC) $MT_2 (+), G (+); MT_2 (-), G (-);$ $MT_2 (+), G (-)$ | I_{GT} | $V_D = 12\text{V}, R_L = 100\Omega,$ | - | 25 | 50 | mA |
| | | | $MT_2 (-), G (+)$ | - | 40 | 75 |
| Gate Trigger Voltage (Continuous DC) $MT_2 (+), G (+); MT_2 (-), G (-);$ $MT_2 (+), G (-)$ | V_{GT} | $V_D = 800\text{V}, R_L = 100\Omega,$ | - | 1.1 | 2.0 | V |
| | | | $MT_2 (-), G (+)$ | - | 1.3 | 2.5 |
| Gate Non-Trigger Voltage $MT_2 (+), G (+); MT_2 (-), G (-);$ $MT_2 (+), G (-)$ | V_{GD} | $V_D = 800\text{V}, T_J = +125^\circ\text{C}, R_L = 10\text{k},$ | 0.2 | - | - | V |
| | | | $MT_2 (-), G (+)$ | 0.2 | - | - |
| Holding Current | I_H | $V_D = 12\text{V},$ Gate Open | - | 30 | 75 | mA |
| Gate Controlled Turn-On Time | t_{gt} | $V_D = 800\text{V}, I_{TM} = 56\text{A}$ (Peak), $I_{GT} = 200\text{mA}$ | - | 1.5 | - | μs |
| Critical Rate of Rise of Off-State Voltage | dv/dt | $V_D = 800\text{V},$ Exponential Waveform, $T_C = +125^\circ\text{C}$ | - | 50 | - | $\text{V}/\mu\text{s}$ |
| Critical Rate of Rise of Commutation Voltage | $dv/dt(c)$ | $V_D = 800\text{V}, I_{TM} = 56\text{A}$ (Peak), Commutating $di/dt = 13.4\text{A}/\text{ms},$ Gate Unenergized, $T_C = +75^\circ\text{C}$ | - | 5 | - | $\text{V}/\mu\text{s}$ |

Note 3. Pulse Width $\leq 2\text{ms}$, Duty Cycle $\leq 2\%$.

