



- NOTES:**
- MATERIAL**
1. Insulator Material: Black, NYLON+G/F UL 94V-0^②
 2. Contact Material: Copper Alloy
 - ② 3. Plating: 1u" Gold Plating
 4. Waterproof Rate: IP67
 5. Do Mating Test After Glued
 6. Applicable Wire Range: 22AWG-26AWG
- ② **Electrical**
1. Contact resistance: 20mΩ max.
 2. Insulation resistance: 500MΩ min. at DC500V
 3. Dielectric withstanding voltage: 500V AC 1 minute
 4. Rating current: 2A
 5. Durability: 500 cycles
 6. Temperature range: -20°C ~ +85°C

F

RoHS compliant
Unit: mm

Scale	Free						Date	Name	Customer-No.	
TOLERANCE						Drawn	24.12.2008	JACK	ASSMANN WSW-No. A-DF 25 LL-WP	
X.X	±0.25					Approved	24.01.2018	Amy		
X.XX	±0.10									
X.XXX	±0.05									
DIM	TOL	②	Add notes	24.01.2018	Segal	ASSMANN WSW components			Drawing-No.	
		①	Drawn	24.12.2008	JACK				ASS 3260 CO	rev02
Angle	±1°	Id.	Modification	Date	Name				Replace	Sheet

H