

RoHS Compliant



Specifications

Electrical Ratings	50mA @ 50VDC
Electrical Life	100,000 cycles typical
Contact Resistance	<50mΩ initial
Actuation Force	180 ± 50gF
Acutation Travel	.30 ± .1mm

Dielectric Strength	250Vrms min
Insulation Resistance	>100MΩ min
Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C

Materials

Actuator	6/6 Nylon		
Housing	6/6 Nylon		
Cover	Stainless Steel		
Contacts	Phosphor Bronze, Silver Plated		
Terminals	Brass, Silver Plated		

Ordering Information

1. Series	CT1103	G	F180	C141
CT1103				
2. Actuator Options A B C T G E				
3. Actuation Force: F180 = 180gF				
4. Cap C11 C12 C13 C16 C18	C19 C22 C26	Cap Colors: **See Cap Options for color availability **Caps available with G actuator only		

www.citrelay.com phone - 763.535.2339 fax - 763.535.2194



Dimensions



Schematic & PC Layout





page 2

www.citrelay.com phone - 763.535.2339 fax - 763.535.2194

Dimensions shown in mm. Dimensions are shown for reference purposes only.



Cap Options for G Actuator



C11_ 1 = White, 2 = Black, 3 = Red, 9 = Light Gray Contact Factory for other available colors



C16_ 1 = White, 2 = Black, 3 = Red, 7 = Blue Contact Factory for other available colors



C22_ 2 = Black, 8 = Dark Gray, 9 = Light Gray Contact Factory for other available colors



C12_ 1 = White, 2 = Black, 3 = Red, 9 = Light Gray Contact Factory for other available colors



C18_ 1 = White, 2 = Black, 3 = Red, 9 = Light Gray Contact Factory for other available colors



C26_ 1 = White, 2 = Black, 3 = Red, 9 = Light Gray Contact Factory for other available colors



C13_





C19_ 1 = White, 2 = Black, 3 = Red, 8 = Dark Gray Contact Factory for other available colors

1 = White, 2 = Black, 3 = Red, 9 = Light Gray Contact Factory for other available colors